

FORCE 145 PLASTIC CARRY CASE



WITH MASK
CARRY CASE
ACCESSORIES



- Direct current (DC) MMA electrode inverter welding machine, 130A. Supplied with welding accessories and plastic carry case.
- Usable electrodes: rutile, basic, stainless steel, cast iron, etc. up to 3,2 mm.
- Advanced arc control devices: arc force, hot start, anti-stick.
- Thermostatic, overvoltage, undervoltage, overcurrent protection. Compatible for use with the motor generator (230V, +/- 15%).-
- High stability of the welding current in power supply voltage variations.
- Light and compact. Easy to transport. Contained consumption thanks to inverter technology.

DESCRIPTION

MMA inverter, electrode welding machine in direct current (DC).

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Compact and light
- High welding current stability in spite of mains voltage fluctuations
- Arc force, hot start and anti-stick devices
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections

Complete with MMA welding accessories and plastic carry case.



TECHNICAL DATA

CODE CODE 815856	V_{1PH} SINGLEPHASE MAINS VOLTAGE 230 V	F MAINS FREQUENCY 50 / 60 Hz
A_{MIN} / A_{MAX} / DC CURRENT RANGE IN DC 10 - 130 A	TELWIN % USE 20°C %USE (20°C USE) (*) 60% @ 125A	A_{MAX} 40°C DC MAX CURRENT DC EN60974-1 125 @ 7% A
V₀ DC MAX NO LOAD VOLTAGE IN DC 72 V	A_{MAX} MAX ABSORBED CURRENT 27 A	P_{MAX} MAX ABSORBED POWER 3,5 kW
P_{MIN} GEN MOTORGNER. MINIMUM POWER 5 kW	η EFFICIENCY 82 %	φ POWER FACTOR(cosphi) (cosphi) 0,6
∅_{MIN} / ∅_{MAX} / DC D.USABLE ELECTRODES IN DC 1,6 - 3,2 mm	IP PROTECTION DEGREE IP21	LxWxH DIMENSIONS (LxWxH) 38 x 42 x 17 cm
kg WEIGHT 5,2 kg	% USE (*)%USE: Dato ideato da TELWIN,	% USE (*)%USE: non presente nella EN 60974-1

SUPPLIED ACCESSORIES



PLASTIC CARRY CASE
322800



DALLAS 300 ELECTRODE HOLDER 300A
712260



TOLEDO 250 WORK CLAMP 250A
712030



CABLE 16 MMQ 1,8 M - PLUG ATLAS 25
124508



SLAG REMOVER
712139

ON REQUEST ACCESSORIES



RUTILE ELECTRODES D. 2 MM 15
PCS
802617



RUTILE ELECTRODES D. 2,5 MM
15 PCS
802618



RUTILE ELECTRODES D. 3,2 MM
10 PCS
802619



STAINLESS STEEL ELECTRODES D.
3,2 MM 8 PCS
802624



RUTILE ELECTRODES D. 2 MM 2,5
KG
802737



RUTILE ELECTRODES D. 2,5 MM
2,5 KG
802739



RUTILE ELECTRODES D. 3,2 MM 4
KG
802749

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



BROCHURE



CERTIFICATE

ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00

Вс.: с 10:00 по 16:00

КОНТАКТЫ:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: <https://storgom.ua/product/svarochnyi-invertor-telwin-force-145.html>

Другие товары: <https://storgom.ua/inventory.html>